



# INTEGRAL TECHNOLOGIES

## CC-DCF-XX

### Dome Camera Fixed DSP

---



TYPE A



TYPE B

#### Specifications

- IMAGE SENSOR: 1/3" Sony Color CCD
- CCD TOTAL PIXELS: NTSC: 537 (H)X505 (V) PAL: 537 (H) X597 (V) (420 TVL)  
NTSC: 811 (H)X508 (V) PAL: 795 (H)X596 (V) (520 TVL)
- SCANNING SYSTEM: NTSC: 525 lines, 60 fields/sec PAL: 625 lines, 50 fields/sec
- SYNC SYSTEM: Internal
- MINIMUM ILLUMINATION: 0.5 Lux F1.2 (A/B), 0 Lux (B) (IR on)
- RESOLUTION: 420 or 520 TV lines depending on the model
- WHITE BALANCE/ GAIN CONTROL/ B.L.C. FUNCTION : AUTO
- S/N RATIO: 48dB (AGC OFF)
- ELECTRONIC SHUTTER: NTSC: 1/60~1/120,000 sec. PAL: 1/50~1/120,000 sec.
- VIDEO OUTPUT: Composite 1.0V p-p at 75 ohm
- GAMMA CORRECTION: 0.45
- LENS: 3.6mm Board Lens (other focal lengths on request)
- OPERATION TEMPERATURE:-10 C TO 50 C
- OPERATIONAL HUMIDITY: within 85%RH
- POWER SUPPLY: DC12V±1V / 100mA (A), 290 mA (B)
- DIMENSIONS: (D x H): 100X75mm (A), 119X110mm (B)
- NET WEIGHT: 540g (A), 900 g (B)
- MODELS AVAILABLE : 1) CC-DCF-4A : Type A, 420 TVL  
2) CC-DCF-5A : Type A, 520 TVL  
3) CC-DCF-4B : Type B, 420 TVL  
4) CC-DCF-5B : Type B, 520 TVL